

## Microfon condensadro de solapaC 417

<b>Polar pattern</b>	omnidirectional
<b>Frequency range</b>	20 to 20,000 Hz
<b>Sensitivity</b>	10 mV/Pa (-40 dBV)
<b>Max. SPL</b>	118/126 dB (for 1%/3% THD)
<b>Equivalent noise level</b>	34 dB-A
<b>Signal/noise ratio (A-weighted)</b>	60 dB
<b>Impedance</b>	200 ohms
<b>Recommended load impedance</b>	1000 ohms
<b>Supply voltage</b>	9 to 52 V phantom power to DIN 45596 or battery powering from B 29 L or AKG bodypack transmitters
<b>Current consumption</b>	approx. 2.2 mA
<b>Connector</b>	C 417 PP: 3-pin XLR, C 417 L: 3-pin mini XLR
<b>Cable</b>	C 417 PP: 3 m (10 ft.), C 417 L: 1.5 m (5 ft.)
<b>Finish</b>	matte black
<b>Dimensions</b>	7.5 dia. x 15 mm / 0.3 x 0.6 in.
<b>Net weight</b>	C 417 PP: 68 g / 2.4 oz., C 417 L: 8 g / 0.3 oz.
<b>Shipping weight</b>	C 417 PP: 220 g / 8.1 oz., C 417 L: 160 g / 5.9 oz.